

K)

PLACE TYPES ▶

P2


P3

P4

P5

SPECIFICATIONS ▼

MONUMENT



P

- a. **Quantity:** 1 max per Frontage
- b. **Height:** 35 ft max. in P5 on SH 71 *see v
20 ft max in P5 on SH 95 & Loop 150
6 ft max in P5
- c. **Max Height to width ratio:** 4:1

DESCRIPTION

A Sign permanently affixed to the ground at its base or by poles that are enclosed by natural stone, stucco, brick, or wood and not mounted to a part of a Building. Pole(s) may be used to construct a Monument Sign so long as the poles are not visible below the Sign.

SIGN DETAILS

- i. A Monument Sign can be defined as a ground Sign generally having a low profile with little or no Open Space between the ground and the Sign and having a Structure constructed of masonry, wood, or materials similar in appearance.
- ii. How to Measure:
 - (1) Maximum total Height is measured from the finished grade at the center of the Sign. If the finished grade at the center of the Sign is higher than the finished grade of the closest paved surface, then the Height shall be measured from the finished grade of the closest paved surface.
 - (2) The monument base shall be a maximum of 2 feet in Height and shall be included in the calculation of total Height.
 - (3) A Monument Sign width cannot exceed 2 times the allowable Sign Height.
- iii. The max Height allowed along SH. 71 is 35 feet. Height limit is 8 feet if Band Sign Height exceeds 4 feet.
- iv. The max Height allowed along Loop 150 and SH 95 is 20 feet. Height limit is 8 feet if Band Sign height exceeds 4 feet.
- v. Signs along SH 71, SH 95 and Loop 150 can be internally illuminated.
- vi. A warrant for internal illumination can be requested.
- vii. Cannot be located within a Sight Triangle.